

TEXWAY

Coarse deniers velour needlepunched carpet
Ideal for high traffic (events, congress...)



1624 Cobalt Blue



1531 Amazonia Green




1486 Beige



1632 Ruby Red




1015 Grey



1005 Dark Grey



1020 Black



1040 Pure Solid Black



Technical data

Surface : coarse deniers velour needlepunch

Backing: back coated

Fibres: 100 % polypropylene

Fibres weight: 600 g/m² ± 10%

Total weight: 730 g/m² ± 10%

Thickness: 5,55 mm

Loose laid or stuck with acrylic emulsion



Stock positions and references

| Coloris / Colours / Farben | 2 m x 30 m | 4 m x 30 m |
|----------------------------|--------------------|--------------------------|
| 1005 Dark Grey | BEXIW1005C2 | BEXIW1005C4 |
| 1015 Grey | BEXIW1015C2 | mini 1400 m ² |
| 1020 Black | BEXIW1020C2 | BEXIW1020C4 |
| 1040 Pure Solid Black | BEXIW1040C2 | mini 1400 m ² |
| 1486 Beige | BEXIW1486C2 | BEXIW1486C4 |
| 1531 Amazonia Green | BEXIW1531C2 | BEXIW1531C4 |
| 1624 Cobalt Blue | BEXIW1624C2 | mini 1400 m ² |
| 1632 Ruby Red | BEXIW1632C2 | mini 1400 m ² |

References written in bold are held in stock. Other references on order.

Tolerance: ≤ 10 000 m² : ± 10% ; ≥ 10 000 m² : ± 5%

For more information, please contact our sales team.

07
EN 14041 : 2005
DOP28

23
EN 14041 : 2005
DOPUK28

Loose laid on any A2fl or A1fl class substrate

Formaldehyde E1
No PCP

*Information on the level of emissions of volatile substances in indoor air, with a risk of inhalation toxicity, on a class scale from A+ (very low emissions) to C (high emissions)

TEXWAY-2025-A1-1224 / Credit photos Sommer
Sommer has the right to alter each product specification in order to improve the product according to latest standards.

Collection 2025



Sommer Flooring Ltd
22 Spitfire Close
Coventry – CV5 6UR
www.sommerltd.com

Tel : 024 7798 1711
E-mail : info@sommerltd.com

